

demark LAMBORGHINI CALORECLIMA					
Outdoor model	SMERALDO-C ODU S 18				
Indoor model	SMERALDO-C IDU FLOOR-CEILING18)
Description	Symbol	Unit Value			
indoor	LIIVA EJD/A)		57		
Sound power level at standard rating conditions outdoor	LWA	[dB(A)]	65		
Refrigerant type	-	-		R32	
GWP (1)	GWP	[kgCO2 eq.]		675	
SEER	SEER	-		6,2	
Energy efficiency class in cooling	-	-	A++		
Annual electricity consumption in cooling (2)	QCE	[kWh/a]	305		
Design load in cooling mode	Pdesignc	[kW]	5,4		
SCOP (average heating season)	SCOP/A	-		4,0	
Energy efficiency class in heating (average season)	-	-		A+	
Annual electricity consumption in heating (average season) (3)	QHE	[kWh/a]	1400		
Warmer heating season	-	-		Υ	
Colder heating season	-	-	N		
Design load in heating mode (average season)	Pdesignh	[kW]	4,0		
Declared capacity at reference design condition (heating average season)	-	[kW]	3,6		
Back up heating capacity at reference design condition (heating average season)	-	[kW]	0,40		
Rated current for cooling	-	[A]	6,0		
Rated current for heating	-	[A]	6,6		
Rated capacity for cooling (Rated - min - max)	Prated cooling	[kW]	5,3	2,7	5,9
Rated capacity for heating (Rated - min - max)	Prated heating	[kW]	5,6	2,4	6,3
Rated power input for cooling (Rated - min - max)	PEER	[kW]	1,5	0,7	2,0
Rated power input for heating (Rated - min - max)	PCOP	[kW]	1,5	0,5	1,6
Rated Energy efficiency ratio	EERrated	-	3,64		
Rated Coefficient of performance	COPrated	-	3,71		
Voltage - Frequency - Phase no.	-	[V-Hz-Ph]	220/240	50	1

⁽¹⁾ Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1 kg of CO2, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

- (2) Energy consumption 305 kW/h per year based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.
- (3) Energy consumption 1400 kW/h per year based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.

Contact details for obtaining more information	Ferroli S.p.A. Via Ritonda 78/A 37047 San Bonifacio (VR) Italy



Trademark	LAMBORGHINI CALORECLIMA				
Outdoor model	SMERALDO-C ODU S 24				
Indoor model	SMERALDO-C IDU FLOOR-CEILING24			ļ	
Description	Symbol	Unit Value			
Sound power level at standard rating conditions indoor	LWA	[dB(A)]	63		
outdoor	LWA	[ub(A)]			
Refrigerant type	-	-		R32	
GWP (1)	GWP	[kgCO2 eq.]		675	
SEER	SEER	-		6,3	
Energy efficiency class in cooling	-	-		A++	
Annual electricity consumption in cooling (2)	QCE	[kWh/a]	394		
Design load in cooling mode	Pdesignc	[kW]	7,1		
SCOP (average heating season)	SCOP/A	-	4,1		
Energy efficiency class in heating (average season)	-	-	A+		
Annual electricity consumption in heating (average season) (3)	QHE	[kWh/a]	2015		
Warmer heating season	-	-	Y		
Colder heating season	-	-	N		
Design load in heating mode (average season)	Pdesignh	[kW]	5,9		
Declared capacity at reference design condition (heating average season)	-	[kW]	5,2		
Back up heating capacity at reference design condition (heating average season)	-	[kW]	0,72		
Rated current for cooling	-	[A]	9,0		
Rated current for heating	-	[A]		8,7	
Rated capacity for cooling (Rated - min - max)	Prated cooling	[kW]	6,8	3,2	8,0
Rated capacity for heating (Rated - min - max)	Prated heating	[kW]	7,6	2,7	8,5
Rated power input for cooling (Rated - min - max)	PEER	[kW]	2,1	0,8	2,7
Rated power input for heating (Rated - min - max)	PCOP	[kW]	2,0	0,7	2,9
Rated Energy efficiency ratio	EERrated	-	3,30		
Rated Coefficient of performance	COPrated	-	3,85		
Voltage - Frequency - Phase no.	-	[V-Hz-Ph]	220/240	50	1

⁽¹⁾ Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1 kg of CO2, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

(3) Energy consumption 2015 kW/h per year based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.

Contact details for obtaining more information	Ferroli S.p.A. Via Ritonda 78/A 37047 San Bonifacio (VR) Italy
--	--

⁽²⁾ Energy consumption 394 kW/h per year based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.



rademark LAMBORGHINI CALORECLIMA					
Outdoor model	SMERALDO-C ODU S 36				
Indoor model	SMERALDO-C IDU FLOOR-CEILING36				j
Description	Symbol	Unit Value		Value	
indoor	T III/A I I I I I I I I I I I I I I I I I		64		
Sound power level at standard rating conditions outdoor	LWA	[dB(A)]	70		
Refrigerant type	-	-		R32	
GWP (1)	GWP	[kgCO2 eq.]		675	
SEER	SEER	-		6,4	
Energy efficiency class in cooling	-	-	A++		
Annual electricity consumption in cooling (2)	QCE	[kWh/a]	574		
Design load in cooling mode	Pdesignc	[kW]	10,5		
SCOP (average heating season)	SCOP/A	-	4,1		
Energy efficiency class in heating (average season)	-	-	A+		
Annual electricity consumption in heating (average season) (3)	QHE	[kWh/a]	2937		
Warmer heating season	-	-	Y		
Colder heating season	-	-	N		
Design load in heating mode (average season)	Pdesignh	[kW]	8,6		
Declared capacity at reference design condition (heating average season)	-	[kW]	7,5		
Back up heating capacity at reference design condition (heating average season)	-	[kW]	1,15		
Rated current for cooling	-	[A]	13,6		
Rated current for heating	-	[A]	15,0		
Rated capacity for cooling (Rated - min - max)	Prated cooling	[kW]	10,1	2,7	11,4
Rated capacity for heating (Rated - min - max)	Prated heating	[kW]	11,7	2,8	12,8
Rated power input for cooling (Rated - min - max)	PEER	[kW]	3,1	0,9	4,3
Rated power input for heating (Rated - min - max)	PCOP	[kW]	3,2	0,8	4,0
Rated Energy efficiency ratio	EERrated	-	3,28		
Rated Coefficient of performance	COPrated	-	3,71		
Voltage - Frequency - Phase no.	-	[V-Hz-Ph]	220/240	50	1

⁽¹⁾ Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1 kg of CO2, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

- (2) Energy consumption 574 kW/h per year based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.
- (3) Energy consumption 2937 kW/h per year based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.

Contact details for obtaining more information Ferroli S.p.A. Via Ritonda 78/A 37047 San Bonifacio (VR) Italy



Trademark	LAMBORGHINI CALORECLIMA				1
Outdoor model	SMERALDO-C ODU S 36T				
Indoor model	SMERALDO-C IDU FLOOR-CEILING36				;
Description	Symbol	Unit Value			
Sound power level at standard rating conditions indo	LWA	[dD(V)]	64		
outdo		[dB(A)] 68			
Refrigerant type	-	-		R32	
GWP (1)	GWP	[kgCO2 eq.]		675	
SEER	SEER	-	6,2		
Energy efficiency class in cooling	-	-		A++	
Annual electricity consumption in cooling (2)	QCE	[kWh/a]	592		
Design load in cooling mode	Pdesignc	[kW]	10,5		
SCOP (average heating season)	SCOP/A	-		4,0	
Energy efficiency class in heating (average season)	-	-		A+	
Annual electricity consumption in heating (average season) (3)	QHE	[kWh/a]		3010	
Warmer heating season	-	-		Υ	
Colder heating season	-	-		N	
Design load in heating mode (average season)	Pdesignh	[kW]	8,6		
Declared capacity at reference design condition (heating average season)	-	[kW]	7,4		
Back up heating capacity at reference design condition (heating average season)	-	[kW]	1,20		
Rated current for cooling	-	[A]	6,3		
Rated current for heating	-	[A]	5,5		
Rated capacity for cooling (Rated - min - max)	Prated cooling	[kW]	10,1	2,7	11,8
Rated capacity for heating (Rated - min - max)	Prated heating	[kW]	11,7	2,8	12,8
Rated power input for cooling (Rated - min - max)	PEER	[kW]	3,1	0,9	4,3
Rated power input for heating (Rated - min - max)	PCOP	[kW]	3,1	0,8	4,0
Rated Energy efficiency ratio	EERrated	-	3,26		
Rated Coefficient of performance	COPrated	-	3,73		
Voltage - Frequency - Phase no.	-	[V-Hz-Ph]	220/240 50		3

⁽¹⁾ Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1 kg of CO2, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

(3) Energy consumption 3010 kW/h per year based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.

⁽²⁾ Energy consumption 592 kW/h per year based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.